



AD3000 - Dripless Anti-Corrosion Barrier Film & Undercoating Lubricant

BENEFITS

- Solvent free Contains natural lanolin and wool wax
- WHMIS / OSHA Non controlled, Non hazardous
- Dripless to +42°C
- Repels and resists water washout
- Can be applied over d amp or dry surfaces
- Does not contain tar or asphalt
- Inverted spray valve (360°C
- High viscosity for thicker film application

GENERAL INFORMATION

Rust block clean undercoating for vehicles and equipment. Ideal for coating existing equipment parts and vehicles for extended service life and preventative maintenance. AD3000 may be applied over rust where it penetrates to the base metal, sealing the pores with state of the art corrosion inhibitors, therefore preventing further rust. Excellent for protection of all steel, cast iron, aluminium, brass, rubber bushings, mouldings, plastic and fiberglass. Environmentally safe. Long lasting protection against corrosion.

TECHNICAL DATA

Flash Point: + 280°C Close cup ASTM D93

Pour Point: +10°C High Viscosity: 1000 Cts Specific Gravity: .9025

AD3000 is available in these sizes:

Part # 21514 12 x 350 g aerosol

Part # 22504 4 x 4 L jug Part # 22520 20 L pail Part # 22545 205 L drum

