



QUALITY PRODUCTS SINCE 1919

www.lloydslaboratories.com

CONCRETE REMOVER

TECHNICAL DATA SHEET

BENEFITS

- No acids – hydrochloric, phosphoric, muriatic
- Non fuming
- Biodegradable
- Non corrosive to skin or equipment
- Fast acting
- Acid replacement technology

GENERAL INFORMATION

Used to clean ready mix trucks, mixers, forms, molds, cement buggies, pumps, trowels, screeds, slip-form pavers, augers and more.

- Use full strength.
- Do not wet down concrete before applying
- Do not use on extremely hot surfaces.
- Spray on to thoroughly wet and saturate concrete. Allow to penetrate and soften the concrete. Do not let it dry.
- Continue spraying and let it work for 20 – 30 minutes or until softened and can easily be removed with water spray.
- For cleaning tools and parts, pour enough Concrete Remover in a plastic bucket to cover the tools entirely. Soak until concrete is loosened.
- Wash with water and dry.

TECHNICAL DATA

Colour:	Amber
Toxicity:	Low
pH:	4.5 – 5.5
Specific Gravity:	1.1 – 1.2 grams / cc

Concrete Remover is available in these sizes:

Part # 82104	4 x 4 litre jugs
Part # 82120	20 litre pail
Part # 82145	205 litre drum

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7
Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467
email: sales@lloydslaboratories.com