



QUALITY PRODUCTS SINCE 1919

www.lloydslaboratories.com

Nanolube Diesel Fuel Treatment

TECHNICAL DATA SHEET

BENEFITS

- Cleans fuel systems, filters and tanks.
- Improves combustion to save fuel.
- Lowers emissions and dissolves tank sludge.
- Removes carbon deposits, improves lubricity, and stabilizes fuel with preservative.

GENERAL INFORMATION

Specifically designed to improve lubricity of today's low sulphur diesel and biodiesel blends. Increases fuel stability and reduces polymerization and chaining of waxes and glyceride molecules. Reduces and maintains low exhaust emissions during idle and acceleration. Immediately increases engine performance by increasing cetane and lubricity helping to predetonation and increasing fuel mileage. Regular use cleans and conditions rotary & piston fuel pumps, injectors, piston rings, seals dissolved gum and varnish deposits and dispose of water contamination in the fuel.

DIRECTIONS

Always add to tank prior to filling. This assures good mixing. 18 oz container treats up to 800 litres (180 gallons).

TECHNICAL DATA

Proprietary blend of additives that function to improve the performance of Diesel and Bio Diesel blends.

Nanolube Diesel Fuel Treatment is available in these sizes:

72501	12 x 535 mL (18 oz) can
72520	1 x 20 L (5.25 gal) pail

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7
Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467
email: sales@lloydslaboratories.com