



QUALITY PRODUCTS SINCE 1919
www.lloydslaboratories.com

STRIP-IT

Biodegradable Professional Paint & Coating Removal

TECHNICAL DATA SHEET

BENEFITS

- Biodegradable yet increasingly effective
- No Methylene Chloride or acids
- Thick gel that clings to vertical surfaces
- Strips multiple layers of paint at a time
- Water based – safe for the user
- Industrial strength

GENERAL INFORMATION

Surface temperature should be higher than 20°C. Product will work slower at cool temperatures. Pour product into paint tray or bucket. If slight separation observed – stir until homogenous. If surface has high gloss or is greasy roughen up with light sanding. Coverage: 1.5 – 2.0 sq meters per liter (60 – 70 sq ft/US gal).

Apply thick layer by paint brush or an airless sprayer. Do not allow to dry on surface. If windy or hot - mist water over the surface to reactivate the product. The stripper is designed to remove several layers in one application. Allow 1 to 4 hours for application. If there are too many layers, remove the layers lifted in the first application and reapply the stripper.

The stripped surface must be rinsed with water to remove all residues before repainting. Safe for metal and wood surfaces.

TECHNICAL DATA

pH:	10.0 – 11.0
Appearance:	Viscous liquid
Colour:	Clear translucent
Odour:	Very low

Strip-It is available in these sizes:

Part # 67704	4 x 4 litre jugs
Part # 67720	20 litre pail
Part # 67745	205 litre drum

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7
Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467
email: sales@lloydslaboratories.com