



QUALITY PRODUCTS SINCE 1919
www.lloydslaboratories.com

Synthetic Air Motor Oil

TECHNICAL DATA SHEET

BENEFITS

- Conditioners prevent o rings and seals from drying out
- Prevents sludge buildup
- Cleans rust, sludge and dirt from all tools as it lubricates
- Makes tools easier to use and more energy efficient
- Prolongs life of tools
- When used as a direct replacement for standard hydraulic oil, reductions in typical maintenance cost can be achieved
- Works to -50°C

GENERAL INFORMATION

A high performance, low viscosity formula designed to creep into the internal working of air tools, reduce wear and eliminate noise associated with rough running equipment. Very effective oil with high detergency that cleans as it protects. Specialized humectants absorb over 10% of their weight in water thereby scavenging moisture from the air. Removes trapped moisture from critical components.

TECHNICAL DATA

Specific Gravity:	0.9
Pour Point:	-50°C
Operating Temperature:	-50°C to +120°C
Appearance:	Amber liquid

Air Motor Oil is available in these sizes:

Part # 68008	12 x 237 mL bottle
Part # 68016	12 x 455 mL bottle w/ trigger sprayer
Part # 68020	20 L pail
Part # 68045	205 L drum

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7
Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467
email: sales@lloydslaboratories.com