



QUALITY PRODUCTS SINCE 1919

www.lloydslaboratories.com

White Lithium Grease with PTFE

TECHNICAL DATA SHEET

BENEFITS

- Multipurpose, high temperature, long lasting lubricant
- Easy application, aerosol spray for maximum coverage
- Excellent rust and corrosion inhibitor
- VOC compliant

GENERAL INFORMATION

Sprays on evenly as a liquid and sets up for a thick coating. Will not splatter, melt, run, wash off or freeze.

Industry: Machinery, fans, blowers, roller channels, chains, conveyors, bearings, gears, pneumatic tools, blades and bits.

Automotive: Hinges, locks, latches, seat tracks, strike plates, cables, distributor cams, wiper mechanisms, bolts, bearings, etc.

Marine: Trailer rollers, winches, turnbuckles, shackles, bearings, slides, motor pivot points and all external moving parts.

DIRECTIONS

- Shake well
- Spray parts to lubricate at temperatures above 10°C (50°F)

TECHNICAL DATA

Chemical Type:	Lithium grease
Appearance:	White film
Odour:	Mild
Worked Pentrometer ASTM D-217,mm:	290 to 310
Dropping point ASTM D 566:	193°C (380°F)
Oxidation ASTM D 942 psi:	5.0 max
Rust 3 Bearing ASTM D-1743:	1,1,1
Temperature range:	-10°C to 150°C (-15°F to 300°F)

White Lithium Grease is available in these sizes:

Part # 61514 12 x 300 gram aerosol

Proudly  Canadian

Lloyds Laboratories Inc., 613 Neal Drive, Peterborough, Ontario K9J 6X7

Tel: 705 876-9997 (800) 361-6766 / Fax: 705 876-6467 (866) 876-6467

email: sales@lloydslaboratories.com